



Artikelnummer	Bruchkraft	zulässiger Kettenzug	Gelenkfläche a _k	rechnerisch k _s	rechnerische Gelenkflächenpressung p _l	Teilung P	lichte Weite b ₁	Bolzen Ø d ₁	Buchsen Ø d ₂	Rollen Typ B d ₃	Rollen Typ C d ₄	Rollen Typ D			Laschen					Gewicht kg/m	
	FB min.											d ₅	d ₆	b ₂	b ₃	s/s ₁	h ₁	h ₂	h ₃		
	(N)											(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		(mm)
FV112A63	112.000	18.700	672	6	27,8	63	30,0	16,0	22,0					31,5	36,0	6,0	40,0				8,0
FV112B63	112.000	18.700	672	6	27,8	63	30,0	16,0		32,0				31,5	36,0	6,0	40,0				7,8
FV112A80	112.000	18.700	672	6	27,8	80	30,0	16,0	22,0					31,5	36,0	6,0	40,0				6,7
FV112B80	112.000	18.700	672	6	27,8	80	30,0	16,0		32,0				31,5	36,0	6,0	40,0				7,7
FV112C80	112.000	18.700	672	6	27,8	80	30,0	16,0			55,0			31,5	36,0	6,0	40,0				12,0
FV112D80	112.000	18.700	672	6	27,8	80	30,0	16,0				72,0	87,0	31,5	36,0	6,0	40,0				17,5
FV112E80	112.000	18.700	672	6	27,8	80	30,0	16,0			55,0			31,5	36,0	6,0		50,0	30,0		13,8
FV112A100	112.000	18.700	672	6	27,8	100	30,0	16,0	22,0					31,5	36,0	6,0	40,0				6,2
FV112B100	112.000	18.700	672	6	27,8	100	30,0	16,0		32,0				31,5	36,0	6,0	40,0				7,1
FV112C100	112.000	18.700	672	6	27,8	100	30,0	16,0			55,0			31,5	36,0	6,0	40,0				10,6
FV112D100	112.000	18.700	672	6	27,8	100	30,0	16,0				72,0	87,0	31,5	36,0	6,0	40,0				15,3
FV112E100	112.000	18.700	672	6	27,8	100	30,0	16,0			55,0			31,5	36,0	6,0		50,0	30,0		12,3
FV112A125	112.000	18.700	672	6	27,8	125	30,0	16,0	22,0					31,5	36,0	6,0	40,0				5,7
FV112B125	112.000	18.700	672	6	27,8	125	30,0	16,0		32,0				31,5	36,0	6,0	40,0				6,4
FV112C125	112.000	18.700	672	6	27,8	125	30,0	16,0			55,0			31,5	36,0	6,0	40,0				9,2
FV112D125	112.000	18.700	672	6	27,8	125	30,0	16,0				72,0	87,0	31,5	36,0	6,0	40,0				13,0
FV112E125	112.000	18.700	672	6	27,8	125	30,0	16,0			55,0			31,5	36,0	6,0		50,0	30,0		10,8
FV112A160	112.000	18.700	672	6	27,8	160	30,0	16,0	22,0					31,5	36,0	6,0	40,0				5,3
FV112B160	112.000	18.700	672	6	27,8	160	30,0	16,0		32,0				31,5	36,0	6,0	40,0				5,9
FV112C160	112.000	18.700	672	6	27,8	160	30,0	16,0			55,0			31,5	36,0	6,0	40,0				8,0
FV112D160	112.000	18.700	672	6	27,8	160	30,0	16,0				72,0	87,0	31,5	36,0	6,0	40,0				11,0
FV112E160	112.000	18.700	672	6	27,8	160	30,0	16,0			55,0			31,5	36,0	6,0		50,0	30,0		9,4
FV112A200	112.000	18.700	672	6	27,8	200	30,0	16,0	22,0					31,5	36,0	6,0	40,0				5,0
FV112B200	112.000	18.700	672	6	27,8	200	30,0	16,0		32,0				31,5	36,0	6,0	40,0				5,5
FV112C200	112.000	18.700	672	6	27,8	200	30,0	16,0			55,0			31,5	36,0	6,0	40,0				7,3
FV112D200	112.000	18.700	672	6	27,8	200	30,0	16,0				72,0	87,0	31,5	36,0	6,0	40,0				9,1
FV112A250	112.000	18.700	672	6	27,8	250	30,0	16,0	22,0					31,5	36,0	6,0	40,0				4,7
FV112B250	112.000	18.700	672	6	27,8	250	30,0	16,0		32,0				31,5	36,0	6,0	40,0				5,1
FV112C250	112.000	18.700	672	6	27,8	250	30,0	16,0			55,0			31,5	36,0	6,0	40,0				6,5
FV112D250	112.000	18.700	672	6	27,8	250	30,0	16,0				72,0	87,0	31,5	36,0	6,0	40,0				8,0