



Artikelnummer	Bruchkraft	zulässiger Kettenzug	Gelenkfläche	rechnerisch k ₃	rechnerische Gelenkflächenpressung p _i	Teilung P	lichte Weite b ₁	Bolzen Ø d ₁	Buchsen Ø d ₂	Rollen Typ B d ₃	Rollen Typ C d ₄	Rollen Typ D		Laschen						Gewicht kg/m	
	FB min.		a _k									d ₅	d ₆	b ₂	b ₃	s/s ₁	h ₁	h ₂	h ₃		
	(N)		(mm ²)									(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		(mm)
M160A100	160.000	22.800	918	7	24,8	100	37	18,0	25,0					38,0	43,0	7	50				9,5
M160B100	160.000	22.800	918	7	24,8	100	37	18,0		36				38,0	43,0	7	50				10,9
M160C100	160.000	22.800	918	7	24,8	100	37	18,0			70			38,0	43,0	7	50				18,7
M160D100	160.000	22.800	918	7	24,8	100	37	18,0				85	25,5	38,0	43,0	7	50				19,4
M160E100	160.000	22.800	918	7	24,8	100	37	18,0			70			38,0	43,0	7		70	45,0		19,4
M160A125	160.000	22.800	918	7	24,8	125	37	18,0	25,0					38,0	43,0	7	50				8,7
M160B125	160.000	22.800	918	7	24,8	125	37	18,0		36				38,0	43,0	7	50				9,9
M160C125	160.000	22.800	918	7	24,8	125	37	18,0			70			38,0	43,0	7	50				16,1
M160D125	160.000	22.800	918	7	24,8	125	37	18,0				85	25,5	38,0	43,0	7	50				16,6
M160E125	160.000	22.800	918	7	24,8	125	37	18,0			70			38,0	43,0	7		70	45,0		16,6
M160A160	160.000	22.800	918	7	24,8	160	37	18,0	25,0					38,0	43,0	7	50				8,0
M160B160	160.000	22.800	918	7	24,8	160	37	18,0		36				38,0	43,0	7	50				8,9
M160C160	160.000	22.800	918	7	24,8	160	37	18,0			70			38,0	43,0	7	50				13,8
M160D160	160.000	22.800	918	7	24,8	160	37	18,0				85	25,5	38,0	43,0	7	50				14,2
M160E160	160.000	22.800	918	7	24,8	160	37	18,0			70			38,0	43,0	7		70	45,0		14,2
M160A200	160.000	22.800	918	7	24,8	200	37	18,0	25,0					38,0	43,0	7	50				7,6
M160B200	160.000	22.800	918	7	24,8	200	37	18,0		36				38,0	43,0	7	50				8,3
M160C200	160.000	22.800	918	7	24,8	200	37	18,0			70			38,0	43,0	7	50				12,5
M160D200	160.000	22.800	918	7	24,8	200	37	18,0				85	25,5	38,0	43,0	7	50				13,0
M160E200	160.000	22.800	918	7	24,8	200	37	18,0			70			38,0	43,0	7		70	45,0		12,5
M160A250	160.000	22.800	918	7	24,8	250	37	18,0	25,0					38,0	43,0	7	50				7,2
M160B250	160.000	22.800	918	7	24,8	250	37	18,0		36				38,0	43,0	7	50				7,8
M160C250	160.000	22.800	918	7	24,8	250	37	18,0			70			38,0	43,0	7	50				11,1
M160D250	160.000	22.800	918	7	24,8	250	37	18,0				85	25,5	38,0	43,0	7	50				11,5
M160A315	160.000	22.800	918	7	24,8	315	37	18,0	25,0					38,0	43,0	7	50				6,9
M160B315	160.000	22.800	918	7	24,8	315	37	18,0		36				38,0	43,0	7	50				7,4
M160C315	160.000	22.800	918	7	24,8	315	37	18,0			70			38,0	43,0	7	50				10,0
M160D315	160.000	22.800	918	7	24,8	315	37	18,0				85	25,5	38,0	43,0	7	50				10,3
M160A400	160.000	22.800	918	7	24,8	400	37	18,0	25,0					38,0	43,0	7	50				6,6
M160B400	160.000	22.800	918	7	24,8	400	37	18,0		36				38,0	43,0	7	50				7,0
M160C400	160.000	22.800	918	7	24,8	400	37	18,0			70			38,0	43,0	7	50				9,0
M160D400	160.000	22.800	918	7	24,8	400	37	18,0				85	25,5	38,0	43,0	7	50				9,3
M160A500	160.000	22.800	918	7	24,8	500	37	18,0	25,0					38,0	43,0	7	50				6,6
M160B500	160.000	22.800	918	7	24,8	500	37	18,0		36				38,0	43,0	7	50				6,7
M160C500	160.000	22.800	918	7	24,8	500	37	18,0			70			38,0	43,0	7	50				8,4
M160D500	160.000	22.800	918	7	24,8	500	37	18,0				85	25,5	38,0	43,0	7	50				8,5
M160HTH	210.000	22.800	918	9	24,8																