



Artikelnummer	Bruchkraft	zulässiger Kettenzug	Gelenkfläche	rechnerisch	rechnerische Gelenkflächenpressung	Teilung P	lichte Weite	Bolzen Ø d ₁	Buchsen Ø d ₂	Rollen Typ B d ₃	Rollen Typ C d ₄	Rollen Typ D		Laschen						Gewicht kg/m		
	FB min.		a _k	k ₃	p _l		b ₁					d ₅	d ₆	b ₂	b ₃	s/s ₁	h ₁	h ₂	h ₃			
	(N)		(mm ²)		(N/mm ²)		(mm)					(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		(mm)	
M450A200	450.000	64.000	2.400	7	26,7	200	56	30,0	42,0					60,0	66,0	12	80				23,8	
M450B200	450.000	64.000	2.400	7	26,7	200	56	30,0		60				60,0	66,0	12	80				26,8	
M450C200	450.000	64.000	2.400	7	26,7	200	56	30,0			120			60,0	66,0	12	80				44,9	
M450D200	450.000	64.000	2.400	7	26,7	200	56	30,0				140	37,0	60,0	66,0	12	80				46,9	
M450A250	450.000	64.000	2.400	7	26,7	250	56	30,0	42,0					60,0	66,0	12	80				22,1	
M450B250	450.000	64.000	2.400	7	26,7	250	56	30,0		60				60,0	66,0	12	80				24,5	
M450C250	450.000	64.000	2.400	7	26,7	250	56	30,0			120			60,0	66,0	12	80				38,9	
M450D250	450.000	64.000	2.400	7	26,7	250	56	30,0				140	37,0	60,0	66,0	12	80				40,6	
M450A315	450.000	64.000	2.400	7	26,7	315	56	30,0	42,0					60,0	66,0	12	80				20,6	
M450B315	450.000	64.000	2.400	7	26,7	315	56	30,0		60				60,0	66,0	12	80				22,6	
M450C315	450.000	64.000	2.400	7	26,7	315	56	30,0			120			60,0	66,0	12	80				34,0	
M450D315	450.000	64.000	2.400	7	26,7	315	56	30,0				140	37,0	60,0	66,0	12	80				35,3	
M450A400	450.000	64.000	2.400	7	26,7	400	56	30,0	42,0					60,0	66,0	12	80				19,5	
M450B400	450.000	64.000	2.400	7	26,7	400	56	30,0		60				60,0	66,0	12	80				21,0	
M450C400	450.000	64.000	2.400	7	26,7	400	56	30,0			120			60,0	66,0	12	80				30,0	
M450D400	450.000	64.000	2.400	7	26,7	400	56	30,0				140	37,0	60,0	66,0	12	80				31,0	
M450A500	450.000	64.000	2.400	7	26,7	500	56	30,0	42,0					60,0	66,0	12	80				18,7	
M450B500	450.000	64.000	2.400	7	26,7	500	56	30,0		60				60,0	66,0	12	80				20,1	
M450C500	450.000	64.000	2.400	7	26,7	500	56	30,0			120			60,0	66,0	12	80				27,5	
M450D500	450.000	64.000	2.400	7	26,7	500	56	30,0				140	37,0	60,0	66,0	12	80				28,2	
M450A630	450.000	64.000	2.400	7	26,7	630	56	30,0	42,0					60,0	66,0	12	80				18,0	
M450B630	450.000	64.000	2.400	7	26,7	630	56	30,0		60				60,0	66,0	12	80				19,0	
M450C630	450.000	64.000	2.400	7	26,7	630	56	30,0			120			60,0	66,0	12	80				24,9	
M450D630	450.000	64.000	2.400	7	26,7	630	56	30,0				140	37,0	60,0	66,0	12	80				25,5	
M450A800	450.000	64.000	2.400	7	26,7	800	56	30,0	42,0					60,0	66,0	12	80				17,4	
M450B800	450.000	64.000	2.400	7	26,7	800	56	30,0		60				60,0	66,0	12	80				18,2	
M450C800	450.000	64.000	2.400	7	26,7	800	56	30,0			120			60,0	66,0	12	80				22,8	
M450D800	450.000	64.000	2.400	7	26,7	800	56	30,0				140	37,0	60,0	66,0	12	80				23,3	
M450HTH	585.000	64.000	2.400	9	26,7																	