



| Artikelnummer | Bruchkraft | zulässiger Kettenzug | Gelenkfläche a _k | rechnerisch k ₃ | rechnerische Gelenkflächenpressung p _i | Teilung P | lichte Weite b ₁ | Bolzen Ø d ₁ | Buchsen Ø d ₂ | Rollen Typ B d ₃ | Rollen Typ C d ₄ | Rollen Typ D | | Laschen | | | | | | Gewicht kg/m | |
|---------------|------------|-------------------------|--------------------------------|-------------------------------|---|--------------|--------------------------------|----------------------------|-----------------------------|--------------------------------|--------------------------------|----------------|----------------|----------------|----------------|------------------|----------------|----------------|----------------|-----------------|------|
| | FB min. | | | | | | | | | | | d ₅ | d ₆ | b ₂ | b ₃ | s/s ₁ | h ₁ | h ₂ | h ₃ | | |
| | (N) | | | | | | | | | | | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | | (mm) |
| M56A63 | 56.000 | 8.000 | 320 | 7 | 25,0 | 63 | 24 | 10,0 | 15,0 | | | | | 24,0 | 27,0 | 4 | 30 | | | | 3,2 |
| M56B63 | 56.000 | 8.000 | 320 | 7 | 25,0 | 63 | 24 | 10,0 | | 21 | | | | 24,0 | 27,0 | 4 | 30 | | | | 3,6 |
| M56C63 | 56.000 | 8.000 | 320 | 7 | 25,0 | 63 | 24 | 10,0 | | | 42 | | | 24,0 | 27,0 | 4 | 30 | | | | 6,5 |
| M56D63 | 56.000 | 8.000 | 320 | 7 | 25,0 | 63 | 24 | 10,0 | | | | 50 | 17,0 | 24,0 | 27,0 | 4 | 30 | | | | 6,8 |
| M56E63 | 56.000 | 8.000 | 320 | 7 | 25,0 | 63 | 24 | 10,0 | | | 42 | | | 24,0 | 27,0 | 4 | | 45 | 30 | | 7,2 |
| M56A80 | 56.000 | 8.000 | 320 | 7 | 25,0 | 80 | 24 | 10,0 | 15,0 | | | | | 24,0 | 27,0 | 4 | 30 | | | | 2,9 |
| M56B80 | 56.000 | 8.000 | 320 | 7 | 25,0 | 80 | 24 | 10,0 | | 21 | | | | 24,0 | 27,0 | 4 | 30 | | | | 3,3 |
| M56C80 | 56.000 | 8.000 | 320 | 7 | 25,0 | 80 | 24 | 10,0 | | | 42 | | | 24,0 | 27,0 | 4 | 30 | | | | 5,5 |
| M56D80 | 56.000 | 8.000 | 320 | 7 | 25,0 | 80 | 24 | 10,0 | | | | 50 | 17,0 | 24,0 | 27,0 | 4 | 30 | | | | 5,8 |
| M56E80 | 56.000 | 8.000 | 320 | 7 | 25,0 | 80 | 24 | 10,0 | | | 42 | | | 24,0 | 27,0 | 4 | | 45 | 30 | | 6,2 |
| M56A100 | 56.000 | 8.000 | 320 | 7 | 25,0 | 100 | 24 | 10,0 | 15,0 | | | | | 24,0 | 27,0 | 4 | 30 | | | | 2,7 |
| M56B100 | 56.000 | 8.000 | 320 | 7 | 25,0 | 100 | 24 | 10,0 | | 21 | | | | 24,0 | 27,0 | 4 | 30 | | | | 3,0 |
| M56C100 | 56.000 | 8.000 | 320 | 7 | 25,0 | 100 | 24 | 10,0 | | | 42 | | | 24,0 | 27,0 | 4 | 30 | | | | 4,8 |
| M56D100 | 56.000 | 8.000 | 320 | 7 | 25,0 | 100 | 24 | 10,0 | | | | 50 | 17,0 | 24,0 | 27,0 | 4 | 30 | | | | 5,0 |
| M56E100 | 56.000 | 8.000 | 320 | 7 | 25,0 | 100 | 24 | 10,0 | | | 42 | | | 24,0 | 27,0 | 4 | | 45 | 30 | | 5,5 |
| M56A125 | 56.000 | 8.000 | 320 | 7 | 25,0 | 125 | 24 | 10,0 | 15,0 | | | | | 24,0 | 27,0 | 4 | 30 | | | | 2,6 |
| M56B125 | 56.000 | 8.000 | 320 | 7 | 25,0 | 125 | 24 | 10,0 | | 21 | | | | 24,0 | 27,0 | 4 | 30 | | | | 2,8 |
| M56C125 | 56.000 | 8.000 | 320 | 7 | 25,0 | 125 | 24 | 10,0 | | | 42 | | | 24,0 | 27,0 | 4 | 30 | | | | 4,3 |
| M56D125 | 56.000 | 8.000 | 320 | 7 | 25,0 | 125 | 24 | 10,0 | | | | 50 | 17,0 | 24,0 | 27,0 | 4 | 30 | | | | 4,4 |
| M56E125 | 56.000 | 8.000 | 320 | 7 | 25,0 | 125 | 24 | 10,0 | | | 42 | | | 24,0 | 27,0 | 4 | | 45 | 30 | | 4,9 |
| M56A160 | 56.000 | 8.000 | 320 | 7 | 25,0 | 160 | 24 | 10,0 | 15,0 | | | | | 24,0 | 27,0 | 4 | 30 | | | | 2,4 |
| M56B160 | 56.000 | 8.000 | 320 | 7 | 25,0 | 160 | 24 | 10,0 | | 21 | | | | 24,0 | 27,0 | 4 | 30 | | | | 2,6 |
| M56C160 | 56.000 | 8.000 | 320 | 7 | 25,0 | 160 | 24 | 10,0 | | | 42 | | | 24,0 | 27,0 | 4 | 30 | | | | 3,9 |
| M56D160 | 56.000 | 8.000 | 320 | 7 | 25,0 | 160 | 24 | 10,0 | | | | 50 | 17,0 | 24,0 | 27,0 | 4 | 30 | | | | 4,0 |
| M56A200 | 56.000 | 8.000 | 320 | 7 | 25,0 | 200 | 24 | 10,0 | 15,0 | | | | | 24,0 | 27,0 | 4 | 30 | | | | 2,3 |
| M56B200 | 56.000 | 8.000 | 320 | 7 | 25,0 | 200 | 24 | 10,0 | | 21 | | | | 24,0 | 27,0 | 4 | 30 | | | | 2,5 |
| M56C200 | 56.000 | 8.000 | 320 | 7 | 25,0 | 200 | 24 | 10,0 | | | 42 | | | 24,0 | 27,0 | 4 | 30 | | | | 3,5 |
| M56D200 | 56.000 | 8.000 | 320 | 7 | 25,0 | 200 | 24 | 10,0 | | | | 50 | 17,0 | 24,0 | 27,0 | 4 | 30 | | | | 3,6 |
| M56A250 | 56.000 | 8.000 | 320 | 7 | 25,0 | 250 | 24 | 10,0 | 15,0 | | | | | 24,0 | 27,0 | 4 | 30 | | | | 2,3 |
| M56B250 | 56.000 | 8.000 | 320 | 7 | 25,0 | 250 | 24 | 10,0 | | 21 | | | | 24,0 | 27,0 | 4 | 30 | | | | 2,4 |
| M56C250 | 56.000 | 8.000 | 320 | 7 | 25,0 | 250 | 24 | 10,0 | | | 42 | | | 24,0 | 27,0 | 4 | 30 | | | | 3,2 |
| M56D250 | 56.000 | 8.000 | 320 | 7 | 25,0 | 250 | 24 | 10,0 | | | | 50 | 17,0 | 24,0 | 27,0 | 4 | 30 | | | | 3,3 |